

D8041C

9VDC to 56VDC, Rugged 5 port Industrial Gigabit Ethernet Switch

4x10/100/1000M TX + 1 Giga TX/ 100/1000M SFP Combo

Operating temp: -40°C to +75°C

OEM/ODM Options



Black



White

Available Case color



D8041C

Models also available:

D8041F --- 4 port Giga TX + 1x100/1000 SFP

D8041T --- 5 port Giga TX

Introduction

This rugged designed industrial Ethernet switch is an ideal solution for Industrial Automation, IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device to connect to end device, and it also can be used to cascaded/daisy-chain to other devices to cover wider area through the optional SFP connection.

Specification

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Ethernet IEEE802.3x Flow Control and Back Pressure,
Switch Architecture	Back-plane (Switching Fabric): 10Gbps
Data Processing	Store and Forward
Flow Control:	IEEE 802.3x Flow Control and Back Pressure
Jumbo Frame	9KB
MAC address Table Size	1K
Packet Buffer Size	1M
Network Connector :	5xRJ-45 10/100/1000BaseT(X) auto negotiation, Auto MDI/MDI-X function, Full/Half duplex 1x SFP 100/1000M BaseX
Network Cable	UTP/STP above Cat.5e Cable
	EIA/TIA-568 100-ohm (100m)
	Fiber Cable (Multi-mode):50/125um,62.5/125um Fiber Cable (Single-mode): 9/125um
Protocol	CSMA/CD
LED	PW1(Power 1) Green, PW2(Power 2) Green, ERR(Fault) Amber,
	TX/RJ-45 port: LNK (Link/Active) Green, SPD(Speed) 10/100(OFF) ,1000 (Green)
	SFP Fiber Per port: Link (Green) Active Flash
DIP Switch	DIP 1: OFF: Port 5 SFP (DEFAULT) ON: Port 5 TX DIP 2: OFF: SFP 1000M (DEFAULT) ON: SFP 100M
Reserve polarity protection	Present
Overload current protection	Present
Power Supply	Redundant Dual DC 9V-56V Power Input
Power Consumption	5.76W@48 VDC full load

Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC, Relay in short circuit mode when 2 powers are connected. in open circuit mode when only one power supply is connected
Removable Terminal Block	Provide 2 Redundant power ,Alarm relay contact ,6 Pin Wire range: 0.34mm ² to 2.5mm ² Solid wire (AWG):12-24/14-22 Stranded wire(AWG): 12-24/14-22 Torque:5lb-In/0.5Nm/0.56Nm Wire Strip length: 7-8mm
Operating Temperature	-40°C-75°C fully tested.
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40°C-85°C
MTBF (mean time between failure)	510,304 hrs (MIL-HDBK-217F) at 25°C
Housing	Rugged Metal ,IP30 Protection
Case Dimension (L x W x D)	142mmx43mmx105mm (LxWxD)
Installation mounting	DIN Rail mounting and Wall Mounting
Certifications:	
EN55022/24	ITE equipment
EN50155	Railways Applications Electronic Equipment used on Rolling Stock
EN55011	Industrial, Scientific and Medical (ISM) equipment
EN50121-3-2	Railway Applications – Electromagnetic Compatibility – Part 3-2 Rolling Stock - Apparatus
EN50121-4	Railway Applications – Electromagnetic Compatibility – Part4 Emissions and Immunity of the Signaling and Telecommunications Apparatus
Safety	IEC EN60950-1
EMC/EMS	CE, FCC, VCCI
EMI	FCC Part 15 Subpart B Class A, CE EN 55022 Class A
EN 50155 / EN 60068-2-6	Vibration
EN 50155 / EN 60068-2-27	Shock
EN 50155 / EN 60068-2-32	Free Fall

Housing Dimension

