

H8080A

Rugged Industrial 8 port 10/100M POE Injector, with 8x10/100 TX PSE
30Watts (802.3af/at POE+), 44-56VDC input,
Operating temp: -40°C to +75°C

Models also available:

H8080A	8 port 10/100M POE+ Injector, with 8x10/100TX PSE(POE+)
H8080A-4P	8 port 10/100M POE+ Injector, with 4x10/100TX PSE(POE+) + 4x10/100TX
D8080A	8 port 10/100M Industrial Ethernet Switch, with 8x10/100TX



H8080A

Introduction

This 10/100M industrial 8 port high power POE switch is equipped with 8 port 30Watts PSE. It is designed for 44-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks, and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

Specification

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE802.3x Flow Control and Back Pressure, IEEE802.3af for POE IEEE802.3at for POE+
Switch Architecture	Back-plane (Switching Fabric): 1.6Gbps
Data Processing	Store and Forward
Flow Control:	IEEE 802.3x Flow Control and Back Pressure
MAC address Table Size	1K
Packet Buffer Size	1M
Network Connector :	8xRJ-45 10/100BaseT(X) auto negotiation, 8 x POE+ 802.3at/af PSE port Auto MDI/MDI-X function, Full/Half duplex
Network Cable	UTP/STP above Cat.5e Cable
	EIA/TIA-568 10-ohm (100m)
Protocol	CSMA/CD
LED	PW1(Power 1) Green, PW2(Power 2) Green, SW(relay) Amber,
	TX/RJ-45 port: LNK (Link/Active) Green, Amber: POE Detected
Housing	Heavy Metal Housing
Reserve polarity protection	Present
Overload current protection	Present
Power Supply	Redundant Dual DC 44V-56V Power Input POE input 44-56VDC
Power Consumption	5.76W@48 VDC full load, Without POE

Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC, Relay in short circuit mode when 2 powers are connected. in open circuit mode when only one power supply is connected
POE power	POE power per port 30watts. Maximum 36Watts Maximum total power 200Watts, Supports IEEE802.3af/at
Removable Terminal Block	Provide 2 Redundant power , Alarm relay contact ,6 Pin Wire range: 0.34mm ² to 2.5mm ² Solid wire (AWG):12-24/14-22 Stranded wire(AWG): 12-24/14-22 Torque:5lb-In/0.5Nm/0.56Nm Wire Strip length: 7-8mm
Operating Temperature	-40°C~75°C fully tested.
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40°C~85°C
MTBF (mean time between failure)	510,304 hrs (MIL-HDBK-217F) at 25°C
Housing	Rugged Metal ,IP30 Protection
Case Dimension (L x W x D)	142mmx36.2mmx105mm (LxWxD)
Installation mounting	DIN Rail mounting and Wall Mounting
Certifications:	
EN55022/24	ITE equipment
EN50155	Railways Applications Electronic Equipment used on Rolling Stock
EN55011	Industrial, Scientific and Medical (ISM) equipment
EN50121-3-2	Railway Applications – Electromagnetic Compatibility – Part 3-2 Rolling Stock - Apparatus
EN50121-4	Railway Applications – Electromagnetic Compatibility – Part4 Emissions and Immunity of the Signaling and Telecommunications Apparatus
Safety	IEC EN60950-1
EMC/EMS	CE, FCC, VCCI
EMI	FCC Part 15 Subpart B Class A, CE EN 55022 Class A
EN 50155 / EN 60068-2-6	Vibration
EN 50155 / EN 60068-2-27	Shock
EN 50155 / EN 60068-2-32	Free Fall

Housing Dimension

